

Tornado 100 TN-TB

H 193
P 52 • 67
L 100

Frozen Food - Food & Beverage

	TN Chiller	TB Freezer	TB/TN Dual Temp
RS-Static			
RV-Ventilated			•
TCS-Heated			
CH-Chocolate			

Installation Plug-in	Front glass Heated double glass	Installazione Plug-in	Vetro frontale Vetro camera riscaldato	Internal color Colore interno
Temperature • -18 / -16 °C (TB-TN / TB-TB) • -1 / +5 °C (TN / TB-TN)	Side panels/Structure Insulated white prepainted sheet	Temperatura • -18 / -16 °C (TB-TN / TB-TB) • -1 / +5 °C (TN / TB-TN)	Fianchi/Struttura Coibentati in lamiera preverniciata bianca	☐ White
Refrigerant R290	Internal base White prepainted sheet	Refrigerante R290	Interno Lamiera preverniciata bianca	Front color Colore frontale
Refrigeration Ventilated	Opening system Self-closing swing open door	Refrigerazione Ventilata	Apertura Porta a battente autochiudente	☐ White
Compressor Hermetic	Lighting Led 5700 K	Compressore Ermetico	Illuminazione Led 5700 K	Sides color Colore fianchi
Defrost • Hot gas (TB) • Off cycle (TN)	Shelves 5 - 10	Sbrinamento • Gas caldo (TB) • Fermata compressore (TN)	Ripiani 5 - 10	☐ White
Climate class 4	Equipment handling Unidirectional runners with adjustable feet	Classe climatica 4	Movimentazione Pattini unidirezionali con piedini regolabili in altezza	



Tornado 100 TN-TB	TB-TN	TN-TN	TB-TB
External dimensions (LxDxH) Dimensioni esterne (LxPxH)	1340x825x1960 mm	1340x825x1960 mm	1340x825x1960 mm
Capacity (gross/net) Capacità (lorda/netta)	1060 / 670 Lt		
Net weight Peso netto	295 kg		
Refrigeration Refrigerazione	Ventilated Ventilata		
Refrigerant Refrigerante	R290		
Climate class Classe climatica	4		
Operating conditions Condizioni ambientali	30 °C / 55 %RH		
Product temperature Temperatura prodotto	-18 / -16 °C (TB) -1 / +5 °C (TN)	-1 / +5 °C	-18 / -16 °C
Compressor (type) Compressore (tipologia)	Hermetic - 2 Ermetico - 2		
Defrost Sbrinamento	Hot gas (TB) / Off cycle (TN) Gas caldo (TB) / Ferm. compr. (TN)	Off cycle Fermata compressore	Hot gas Gas caldo
Power supply Alimentazione	230 V / 1 Ph / 50 Hz		
Electrical input (nominal) Assorbimentonto elettrico (regime)	1650 W / 8,9 A	750 W / 4,1 A	1740 W / 8,6 A
Electrical input (defrost) Assorbimento elettrico (sbrinamento)	1800 W / 11,8 A	160 W / 1 A	2840 W / 13,4 A

Technical sheet about models whit condensing unit included with air cooled
Dati tecnici riferiti a modelli con unità a bordo con condensazione ad aria

Accessorio Item			
Grid (532 x 505 mm) Griglia	5+5	5+5	5+5

